

## TUMBLE DRYERS

# LDR220, LDR270, LDR350, LDR490

### FEATURES

- Easy to use timer
- SAFETEC TM Fire Supression System
- Electrical, Gas, and Steam heating
- Galvanised, Reversing Drum
- Large door opening for easy loading and unloading
- Axial airflow
- Large lint filter
- Full OPL microprocessor control
- Residual moisture control Sensodry+ ®  
(= lower energy, utility and linen replacement costs)

### OPTIONS

- Stainless steel drum
- Stainless steel front panel
- Coin operated version
- Extended warranty
- Rental option



| TYPE                      |        | LDR220   | LDR270        | LDR350        | LDR490        |
|---------------------------|--------|--|---------------|---------------|---------------|
| <b>CAPACITY</b>           |        |  |               |               |               |
| Capacity                  | kg     | 11,5   | 13,5          | 16            | 24            |
| Drum volume               | l      | 217  | 271           | 347           | 491           |
| Drum diameter             | mm     | Ø673   | Ø673          | Ø762          | Ø838          |
| <b>AIRFLOW</b>            |        |  |               |               |               |
| 50 Hz                     | l/s    | 203  | 203           | 260           | 283           |
| 60 Hz                     | l/s    | 236  | 236           | 307           | 330           |
| <b>DRYING AVERAGE</b>     |        |  |               |               |               |
| Gas heating               | g/min  | 222  | 258           | 331           | 444           |
| Electric heating          | g/min  | 172  | 272           | 335           | 399           |
| <b>MOTOR</b>              |        |  |               |               |               |
| Fan                       | kW     | 0,187  | 0,187         | 0,187         | 0,375         |
| Drive                     | kW     | 0,187  | 0,187         | 0,187         | 0,375         |
| <b>GAS HEATING</b>        |        |  |               |               |               |
| Energy                    | kW     | 18,8   | 21,4          | 26,4          | 29,9          |
| Energy                    | kBTU/h | 64   | 73            | 90            | 102           |
| Electrical connection     |        | 1×200-240V 50/60Hz, 3×200-240V 50/60Hz<br>3×380-415V 50Hz, 3×380-415/440V 60Hz |               |               |               |
| Gas connection            | NPT    | ½"   | ½"            | ½"            | ½"            |
| <b>STEAM HEATING</b>      |        |  |               |               |               |
| High pressure 6,9 bar     | kW     | 39,6   | 39,5          | 48,6          | -             |
|                           | kBTU/h | 135  | 134,7         | 166           | -             |
| Electrical connection     |        | 1×200-240V 50/60Hz, 3×200-240V 50/60Hz<br>3×380-415V 50Hz, 3×380-415/440V 60Hz |               |               |               |
| Steam connection          | NPT    | ¾"   | ¾"            | ¾"            | -             |
| <b>ELECTRICAL HEATING</b> |        |  |               |               |               |
| Energy                    | kW     | 12   | 21            | 24            | 27            |
| Electrical connection     |        | 3×200-240V 50/60Hz, 3×380-415 50Hz, 3×380-415/440V 60Hz                        |               |               |               |
| <b>EXHAUST</b>            |        |  |               |               |               |
|                           | Ø/mm   | 152  | 152           | 203           | 203           |
| <b>DIMENSIONS</b>         |        |  |               |               |               |
| H×W×D                     | mm     | 1622×711×1038  | 1622×711×1191 | 1622×800×1191 | 1695×876×1362 |
| Net weight                | kg     | 137  | 150           | 164           | 197           |
| <b>TRANSPORT DATA</b>     |        |  |               |               |               |
| Gross weight              | kg     | 151  | 165           | 179           | 216           |
| Packing H×W×D             | mm     | 1753×762×1092  | 1753×762×1245 | 1753×838×1245 | 1829×902×1489 |

